

12

EUROPEAN PATENT APPLICATION

21 Application number: 88304954.6

51 Int. Cl.: **G 01 F 1/36**
G 01 F 1/40

22 Date of filing: 31.05.88

30 Priority: 02.06.87 GB 8712851

43 Date of publication of application:
07.12.88 Bulletin 88/49

84 Designated Contracting States: DE FR GB IT

71 Applicant: **FLUID DEVICES LIMITED**
16, Brook Gardens
Kingston-upon-Thames Surrey, KT2 7ET (GB)

72 Inventor: **Larner, Donald Alexander**
16 Brook Gardens
Kingston Upon Thames, Surrey KT2 7ET (GB)

74 Representative: **White, Martin David et al**
MARKS & CLERK 57/60 Lincoln's Inn Fields
London WC2A 3LS (GB)

54 Transducer for fluid flow.

57 A flow transducer for producing a pressure differential responsive to rate of fluid flow comprises:- a housing (10) forming a flow passage (11a, 11b) for the fluid; said passage (11a, 11b) having disposed therein a parallel throat (13) which enlarges in the downstream direction into a chamber (14); a closely fitting yet freely sliding piston (16) disposed within the chamber and having an axial opening (18) for the flow of fluid; a valve member (19) of substantially conical form located and supported in the chamber (14) for obturating the upstream end of the said axial opening (18) when there is no flow; the said conical valve member (19) extending the the downstream direction nose first into the said axial opening (18) to provide a variable annular orifice (21) for fluid flow, the area of said orifice (21) increasing progressively with increasing axial displacement of the said sliding piston (16) in the downstream direction; an axially extending coil spring (23) for biasing the sliding piston (16) in an upstream direction to tend to reduce the area of the variable annular orifice (21) formed between the piston (16) and the valve member (19); the housing (10) having two pressure tapings (24a, 24b) therein at positions respectively upstream and downstream of the variable annular orifice (21) for the detection of a pressure differential induced by fluid flow; the said upstream pressure tapping (24a) communicating with an annular chamber (25) surrounding the throat (13); a plurality of

radial holes (26) in an annular arrangement opening from the annular chamber (25) into the bore (13) of the throat for the detection of the upstream component of the said pressure differential, the said radial holes (26) being all of the same diameter and in the same axial position relative to the throat (13).

The housing (10) is made in one piece to minimize cost and to avoid possible leakage and fatigue problems such as are commonly encountered in high pressure hydraulic service.

Connecting means (28, 29) are provided at the upstream and downstream ends of the housing in the form of internal screw threads. These threads are of standard size having regard to the maximum flow capacity of the transducer and of the system in which it is fitted; making them internal (as opposed to external) screw threads maximizes the possible internal bore size of the housing for the containment of the working parts of the transducer mechanism and allows of the provision of flow passages of optimum size.

The valve member (19) is of simple frusto-conical form which has the effect of producing a roughly linear relationship between rate of fluid flow and pressure differential. If it should be necessary to produce some other relationship between these variables the longitudinal profile of the valve member (19) may be suitably modified; such a modification might be required

Description

TRANSDUCER FOR FLUID FLOW

This invention relates to a flow transducer for producing a pressure differential responsive to rate of fluid flow.

It is an object of the invention to provide a compact flow transducer of simple and inexpensive construction which will measure with consistent accuracy over a wide flow range.

A further object of the invention is to provide a flow transducer which is particularly suitable for incorporation into a high pressure hydraulic system.

A further object of the invention is to provide a flow transducer which can be serviced in the field by operatives of limited skill and experience without consequent loss of calibration accuracy.

According to the present invention a flow transducer comprises:- a housing forming a flow passage for the fluid; said passage having disposed therein a parallel throat which enlarges in the downstream direction into a chamber; a closely fitting yet freely sliding piston disposed within the chamber and having an axial opening for the flow of fluid; a valve member of substantially conical form located and supported in the chamber for obturating the upstream end of the said axial opening when there is now flow; the said conical valve member extending in the downstream direction nose first into the said axial opening to provide a variable annular orifice for fluid flow, the area of said orifice increasing progressively with increasing axial displacement of the said sliding piston in the downstream direction; an axially extending coil spring for biasing the sliding piston in an upstream direction to tend to reduce the area of the variable annular orifice formed between the piston and the valve member; the housing having two pressure tapings therein at positions respectively upstream and downstream of the variable annular orifice for the detection of a pressure differential induced by fluid flow; the said upstream pressure tapping communicating with an annular chamber surrounding the throat; a plurality of radial holes opening from the annular chamber into the bore of the throat for the detection of the upstream component of the said pressure differential, the said radial holes being all of the same diameter and in the same axial position relative to the throat.

Preferably the housing is made in one piece to minimize cost and to avoid possible leakage and fatigue problems such as are commonly encountered in high pressure hydraulic service.

Preferably connecting means are provided at the upstream and downstream ends of the housing in the form of internal screw threads. If these threads are of standard size having regard to the maximum flow capacity of the transducer and of the system in which it is fitted, making them internal (as opposed to external) screw threads maximizes the possible internal bore size of the housing for the containment of the working parts of the transducer mechanism and allows of the provision of flow passages of optimum size.

Preferably the valve member is of simple frusto-

conical form which has the effect of producing a roughly linear relationship between rate of fluid flow and pressure differential. If it should be necessary to produce some other relationship between these variables the longitudinal profile of the valve member may be suitably modified; such a modification might be required were a more exactly linear relationship be necessary for instance.

Preferably means are provided for the convenient fine adjustment of the initial loading of the piston biasing spring during manufacturing calibration, together with facilities for subsequent disassembly and reassembly of the transducer mechanism in the field without loss of the original calibration.

The invention will be further described by way of example with reference to the accompanying drawings wherein:-

Fig. 1 is a longitudinal section through a flow transducer embodying the invention. The figure shows, above the centreline, the positions of the moving parts at maximum flow and, below the centreline, their positions when little or no flow is taking place; and

Fig. 2 is a section along the line A - A of Fig. 1.

Referring to the drawings, the illustrated flow transducer for producing a pressure differential responsive to rate of fluid flow comprises a one-piece housing 10 forming a flow passage 11 for the fluid (the fluid normally entering at the end 11a and leaving at the end 11b). The passage has inserted therein a throat member 12, the parallel bore 13 of which forms a throat which opens in the downstream direction into a chamber 14 via a number of fixed apertures 15 formed at the downstream end of the throat member 12. A piston 16 is in closely sliding engagement with part 17 of the interior of the chamber 14 and has an axial opening 18 for the flow of fluid. A valve member 19 of substantially conical form is located and supported coaxially with the chamber 14 by an extension 20 of the throat member 12, and extends in the downstream direction (from 11a to 11b) nose first into the axial opening 18. The valve member 19 obturates the axial opening 18 when there is little or no flow taking place. An annular orifice 21 for fluid flow is presented between the conical surface of valve member 19 and the upstream edge 22 of the axial opening 18, the total cross-sectional area of which varies progressively according to the axial position of the piston 16 relative to the valve member. An axially extending coil compression spring 23 is arranged between the piston 16 and a spring seating 31 (see below) for biasing the piston in the upstream direction to tend to close the annular orifice 21. The housing has two pressure tapings 24a, 24b situated respectively upstream and downstream of the annular orifice 21 for detecting a pressure differential induced by fluid flow.

The upstream tapping 24a communicates with the interior 13 of the throat member 12 via an annular chamber 25 of intermediate capacity formed between the throat member 12 and the housing 10 and surrounding the throat 13. A number of relatively small radial holes 26, all of the same diameter and at the same axial location, in an annular arrangement, connect the annular chamber 25 in turn to the parallel bore 13 of the throat member 12.

The effect of the annular chamber 25 is to average the individual and often slightly varying pressures detected by each of the holes 26 and thus compensate in part for any distortions in the transverse velocity profile of the fluid entering the throat member 12 which may have been caused by disturbances in the flow conduits leading to the transducer.

A groove 27 containing an elastomeric O-ring contributes to the proper sealing of the annular chamber 25, as does the use of anaerobic sealant between screw-threads 28, 30 - see below.

Connecting means 28 and 29 are provided at each end of the housing 10 in the form of internal screw threads by means of which the transducer can be incorporated into a hydraulic system (not shown).

As fluid flow through the flow passage from the upstream end 11a to the downstream end 11b increases, the piston 16 moves progressively in a downstream direction to present an increasing annular orifice 21 to fluid flow, at the same time compressing the spring 23. A vary differential pressure is thus induced across the annular orifice 21, according to the load rate of the spring 23 and the longitudinal profile of the valve member 19. This differential pressure is detected by tapings 24a and 24b, in the manner previously described herein, and is led away to a suitable measuring device.

For example, a suitable differential pressure transducer for this purpose is disclosed in European Patent Specification No. 0 119 038 and United States Patent Specification No. 4 523 476.

The shape of the valve member is, as shown in the drawings, conveniently frustro-conical which results in a relationship between flow and pressure differential which is roughly linear. This relationship is adequate where the transducer is used in conjunction with an analogue type readout device (such as a differential pressure dial gauge for instance) which can be calibrated to match. By varying the exact longitudinal profile of the valve member 19, different relationships can be brought about; one such variation would, for instance, result in a more precisely linear relationship such as would be necessary for use in conjunction with a digital readout device.

Fine adjustment of the initial loading of the piston biasing spring 23 during calibration is effected by appropriate axial positioning of the throat member 12, which has male screw

threads formed on part 30 of its exterior for engagement with an extension of the internal connecting thread 28. After such adjustment the throat member is locked and sealed in position by, for instance, the use of an anaerobic locking sealant applied to the threaded part 30 of the throat member.

The downstream end of spring 23 bears upon the above-mentioned spring seating 31, which is itself retained by a circlip 32. By removal of this circlip at any time the working parts of the device may be withdrawn from the housing for cleaning and inspection; subsequent reassembly of the parts and replacement of the circlip restores the original calibration conditions within the transducer.

It has been determined by flow analysis that the maximum diameter of the valve member 19 can be reduced relative to that of the axial opening 18 by an amount which will permit the passage of full rated reverse flow whilst inducing a pressure drop of about 40 bar, without the proportional operating flow range of the transducer being reduced below about 30:1 which is quite acceptable for most industrial applications. In this way, inadvertent reverse flow can be accommodated in a simple manner without destructive effects to the interior parts of the device; it will be appreciated that system operating pressures in this type of application often rise as high as 420 bar or more, and, were no such provision made to accommodate reverse flow, the mechanism would be destroyed.

In a possible general modification, the screw threads 28 and 29 may be replaced by flanges (not shown) for purpose of connecting the transducer into a hydraulic system.

Claims

1. A flow transducer for producing a pressure differential responsive to rate of fluid flow, comprising:- a housing (10) forming a flow passage (11a, 11b) for the fluid; said passage (11a, 11b) having disposed therein a parallel throat (13) which enlarges in the downstream direction into a chamber (14); a closely fitting yet freely sliding piston (16) disposed within the chamber and having an axial opening (18) for the flow of fluid; a valve member (19) of substantially conical form located and supported in the chamber (14) for obturating the upstream end of the said axial opening (18) when there is no flow; the said conical valve member (19) extending in the downstream direction nose first into the said axial opening (18) to provide a variable annular orifice (21) for fluid flow, the area of said orifice (21) increasing progressively with increasing axial displacement of the said sliding piston (16) in the downstream direction; an axially extending coil

spring (23) for biasing the sliding piston (16) in an upstream direction to tend to reduce the area of the variable annular orifice (21) formed between the piston (16) and the valve member (19); the housing (10) having two pressure 5
tappings (24a, 24b) therein at positions respectively upstream and downstream of the variable annular orifice (21) for the detection of a pressure differential induced by fluid flow; the said upstream pressure tapping (24a) communicating with an annular chamber (25) surrounding the throat (13); a plurality of radial 10
holes (26) in an annular arrangement opening from the annular chamber (25) into the bore (13) of the throat for the detection of the upstream component of the said pressure differential, the said radial holes (26) being all of the same diameter and in the same axial position relative to the throat (13). 15

2. A flow transducer as claimed in claim 1 wherein the housing (10) is made in one piece. 20

3. A flow transducer as claimed in claim 1 or 2 wherein connecting means (28, 29) are provided at the upstream and downstream ends of the housing in the form of internal screw 25
threads.

4. A flow transducer as claimed in claim 1, 2 or 3 wherein the valve member (19) is of simple frustro-conical form which has the effect of producing a roughly linear relationship between rate of fluid flow and pressure differential. 30

5. A flow transducer as claimed in any preceding claim wherein means (28, 30) are provided for the convenient fine adjustment of the initial loading of the piston-biasing spring 35
(23) during manufacturing calibration, and means (32) for subsequent disassembly and reassembly of the transducer mechanism without loss of said original calibration. 40

40

45

50



55

60

65

4

0294157





European Patent
Office

EUROPEAN SEARCH REPORT

Application number

EP 88304954.6

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl. 4)
Y	DE - A - 1 773 073 (DOPSLAFF) * Fig. 1-3; page 9 - page 14, paragraph 1 *	1	G 01 F 1/36 G 01 F 1/40
X	-- FR - A - 2 209 925 (RACINE FEDERATED)	2,3	
Y	* Fig. 1,6 *	1	
X	* Fig. 1; page 4, lines 33-36 *	4,5	
	--		
A	DE - A1 - 2 919 192 (SPERRY RAND) * Fig. 1,2 *	1	

The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int. Cl. 4)
			G 01 F 1/00
Place of search VIENNA		Date of completion of the search 09-09-1988	Examiner BURGHARDT
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			